

EVINRUDE® E-TEC® ENGINE SPECIFICATIONS

60 H.O.

Engine Model (Color)	(a) E60HGL Graphite (b) E60HGX Graphite
Engine Type	Inline 3-Cylinder E-TEC D.I.
Bore x Stroke - in (mm)	3.601 x 2.588 (91 x 66)
Displacement - cu in (cc) L	79.1 (1295) 1.3L
Gear Ratio	2.36:1
Full Throttle RPM Range	5000-5500 RPM
Weight - lbs (kg)	(a) 320 (145) (b) 335 (152)
Starting	Electric
Controls	Mechanical
Fuel Induction	E-TEC Direct Injection with stratified low RPM combustion mode
Alternator Output*	81 Amps Total / 25 Net Dedicated
Steering	Remote (Tiller accessory)
Trim Method	Trac-1 Power Trim and Tilt
Trim Range	-4° to 17°
Tilt Range	75°
Shaft Length - in (mm)	(a) 20 (508) (b) 25 (635)
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - gal	2.4 (2.3)
Recommended Oil	Evinrude / Johnson XD-100 Oil
Recommended Fuel	87 Octane
Warranty	3-Year, Non-Declining
Emissions Compliance	EPA 2013 / CARB 3 STAR / European Union



* Variable Voltage Computer Controlled 81 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 25 Amp.

EVINRUDE®

