

# 15 HP

<b>Engine Model (Color)</b>	(a) E15RG4 Graphite (b) E15RGL4 Graphite (c) E15TEG4 Graphite
<b>Engine Type</b>	2-cylinder
<b>Bore x Stroke - in (mm)</b>	2.4 x 2.36 (61 x 60 )
<b>Displacement - cu in (cc)</b>	21.4 (351)
<b>Gear Ratio</b>	2.15:1
<b>Full Throttle RPM Range</b>	5000-6000 RPM
<b>Weight - lbs (kg)*</b>	(a) 114.4 (52) (b) 117 (53) (c) 120 (55)
<b>Starting</b>	(a)(b) Manual (c) Electric
<b>Controls</b>	Mechanical
<b>Fuel Induction</b>	Carbureted
<b>Alternator Output</b>	Only on Electric Models: 12V, 145W, 12A (optional on Electric Start Models)
<b>Steering</b>	(a)(b)(c) Tiller
<b>Trim Method</b>	Manual or Power Tilt
<b>Shaft Length - in (mm)</b>	(a)(c) 15 (381) (b) 20 (508)
<b>Oil Tank Capacity - fl oz (ml)</b>	32 (950)
<b>Recommended Oil</b>	Evinrude/ Johnson 5W40 Ultra 4-Stroke Oil
<b>Recommended Fuel</b>	87 Octane
<b>Warranty</b>	3-Year, Non-Declining
<b>Emissions Compliance</b>	EPA 2013 / CARB 3 STAR
<b>Recommended Fuel</b>	87 Octane
<b>Warranty</b>	3-Year, Non-Declining
<b>Emissions Compliance</b>	EPA 2013 / CARB 3 STAR / European Union

