

9.8 HP

Engine Model (Color)	(a) E10RG4 Graphite (b) E10RGL4 Graphite (c) E10TPL4 Graphite (d) E10PGL4 Graphite
Engine Type	2-cylinder
Bore x Stroke - in (mm)	2.17 x 1.73 (55 x 44)
Displacement - cu in (cc)	12.8 (209)
Gear Ratio	2.08:1
Full Throttle RPM Range	5000-6000 RPM
Weight - lbs (kg)*	(a) 81.5 (37) (b) 84 (38) (c) 102.5 (46) (d) 103.6 (47)
Starting	(a)(b) Rope (c)(d) Electric
Controls	(a)(b)(c) Tiller Handle (d) Mechanical
Fuel Induction	Carbureted
Alternator Output	Only on Electric Models: 12V, 145W, 6A (Standard on Electric Start Models)
Steering	(a)(b)(c) Tiller (d) Remote
Trim Method	(a)(b) Manual (c) Manual or Power (d) Power Tilt
Shaft Length - in (mm)	(a) 15 (381) (b)(c)(d) 20 (508)
Oil Tank Capacity - fl oz (ml)	27 (800)
Recommended Oil	Evinrude/ Johnson 5W40 Ultra 4-Stroke Oil
Recommended Fuel	87 Octane
Warranty	3-Year, Non-Declining
Emissions Compliance	EPA 2013 / CARB 3 STAR
Recommended Fuel	87 Octane
Warranty	3-Year, Non-Declining
Emissions Compliance	EPA 2013 / CARB 3 STAR / European Union

